



NORTH AMERICAN FIRE HOSE

The difference is...*your* margin of safety.

Mil-H-24606B

EPDM Rubber Lining / Polyester Double Jacket
Also available with Polyurethane (TPU) Lining

EPDM Rubber Lined Mil-H-24606B™ FEATURES

- **Poly-Cord™** ring spun polyester warp yarns are combined with filament polyester filler yarns.
- Available with our **Ultra-Shield™** high-performance polyurethane coating applied to seal each and every fiber in the bundle, further improving the abrasion resistance, reducing moisture and chemical absorption, and providing vivid color-coded identification.
- The EPDM rubber lining is unaffected by Ozone deterioration, and is one component in the **Friction Fighter System™**, creating an extremely smooth waterway surface, thereby reducing friction loss and improving nozzle performance.
- **The Dura-Bond™** vulcanized adhesion system, which creates both a mechanical and chemical bond between the EPDM lining and the jacket, reduces the probability of delamination as is experienced with competitive adhesive bonded rubber lined constructions.
- The result is a very strong, flexible, and “Tuff” hose, with good heat and chemical resistance.

- Meets and exceeds all specifications for **Mil-H-24606B EPDM Rubber Lined**

- Both the hose and brass couplings are made and assembled in the USA. Performance shall meet and exceed NFPA 1961 Standards.

Available in 50 foot lengths



 **FAMILY OWNED
AMERICAN MADE**

Hose Specifications for EPDM Rubber Lined

HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 50' CPLD BRASS
1½"	MIL-H-24606B	600 PSI	300 PSI	1 ¹⁵ / ₁₆ "	15 lbs.
1¾"	MIL-H-24606B	600 PSI	300 PSI	2 ³ / ₁₆ "	21 lbs.
2½"	MIL-H-24606B	600 PSI	300 PSI	3"	34 lbs.

Poly-Cord,™ Ultra-Shield,™ Friction Fighter System™ and Dura-Bond™ are all trademarks of North American Fire Hose Corporation.
All rights reserved.

Revision 2019A

NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454

Tel: 805.922.7076 • Fax: 805.922.0086

NAFHC.com

