

The difference is...*your* margin of safety.

Potable Water 800™

Polyurethane (TPU) Lining / Polyester Double Jacket

- The *Dura-Thane*[™] polyurethane inner lining is extremely light weight and compact, and is a National Sanitation Foundation (NSF 60) approved material for safely conveying drinking water.
- Available with standard Blue *Ultra-Shield*[™] high-performance polymeric coating applied to seal each and every fiber in the bundle, further improving the abrasion resistance, reducing moisture and chemical absorption, and providing vivid colorcoded identification.
- The *Friction Fighter System*[™] creates an extremely smooth waterway surface, thereby significantly reducing friction loss and improving flow characteristics.

- **Poly-Cor**d[™] ring spun polyester warp yarns are combined with filament polyester filler yarns.
- With less weight and reduced coil diameters it folds more tightly, while at the same time providing more maneuverability and flexibility than traditional hose types.
- Extremely strong and flexible hose, with good heat and chemical resistance, along with superior flow characteristics
- Potable water hose is made in the USA, and requires domestic brass couplings. Performance shall meet and exceed NFPA 1961 Standards.

Available in 50, 75 and 100 foot lengths





HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 50' UNCPLD
1½"	PH-800	800 PSI	400 PSI	1 ¹⁵ ⁄16"	14 lbs.
1 ³ ⁄4"	PH-800	800 PSI	400 PSI	2 ³ ⁄16"	15.5 lbs.
2"	PH-800	800 PSI	400 PSI	2 1/16"	18 lbs.
2 1/2"	PH-800	800 PSI	400 PSI	3"	23 lbs.
3"	PH-800	800 PSI	400 PSI	317/32"	31 lbs.

Potable Water 800,[™] Industrial Attack Plus-800,[™] IAP-800,[™] PF-800,[™] Poly-Flow 800,[™] Ultra-Shield,[™] Poly-Cord,[™] Friction Fighter System,[™] and Dura-Thane,[™] are all trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2024A

