



Occupant Rack Hose (PR-500™)

Polyurethane (TPU) Lining / Filament Polyester Single Jacket

POLY-RACK 500™ FEATURES

- Synthetic filament polyester wrap and filler yarns are unaffected by the effects of mildew and rot, requiring less maintenance after use.
- The *Dura-Thane*[™] polyurethane inner lining is extremely strong and durable, while maintaining a lightweight and compact profile.
- It is designed for Emergency Fire Protection with water pressures not exceeding 225 PSI per NFPA 1961.
- Occupant Rack Hose (PR-500™) is intended to be used only with Listed hose racks, reels and cabinets where the specific combination of hose and rack, reel or cabinet has been investigated and found acceptable.
- Hose stored on racks or reels shall be protected from the weather and any local environmental condition potentially harmful to the hose.
- Occupant Rack Hose (PR-500[™]) is made and assembled in the USA, available with either imported or domestic couplings in aluminum or brass.
- Performance shall meet and exceed NFPA 1961 Standards.

Available in 50, 75 and 100 foot lengths





** Available with Factory Mutual

 $PR-500, ^{\intercal}M\ Poly-Rack\ 500, ^{\intercal}M\ and\ Dura-Thane ^{\intercal}M\ are\ all\ trademarks\ of\ North\ American\ Fire\ Hose\ Corporation.\ All\ rights\ reserved.$

Revision 2019A

NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454 Tel: 805.922.7076 • Fax: 805.922.0086 NAFHC.com

HOSE SIZE SPECIFICATION NUMBER ACCEPTANCE TEST PSI SERVICE TEST PSI BOWL SIZE WEIGHT PER 50' UNCPLD

11/2" PR-500** 500 PSI 250 PSI 11/16" 5 lbs.