



NORTH AMERICAN FIRE HOSE

The difference is...*your* margin of safety.

Mil-H-24606B

Polyurethane (TPU) Lining / Polyester Double Jacket
Also available with EPDM Rubber Lining

TPU-Lined Mil-H-24606B™ FEATURES

- **Poly-Cord™** ring spun polyester warp yarns are combined with filament polyester filler yarns.
- Available with our **Ultra-Shield™** high-performance polyurethane coating applied to seal each and every fiber in the bundle, further improving the abrasion resistance, reducing moisture and chemical absorption, and providing vivid color-coded identification.
- **The Dura-Thane™** polyurethane inner lining is extremely light weight and compact and is a National Sanitation Foundation (NSF 60) approved material for safely conveying drinking water.
- The result is a very strong, flexible, and “Tuff” hose, with good heat and chemical resistance.
- Meets and exceeds all specifications for **Mil-H-24606B Polyurethane TPU Lined**

- The hose and brass couplings are made in the USA, performance shall meet and exceed NFPA 1961 Standards

Available in 25 and 50 foot lengths



 **FAMILY OWNED
AMERICAN MADE**

Hose Specifications for TPU-Lined

HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 50' CPLD BRASS
1½"	MIL-H-24606B-TPU	600 PSI	300 PSI	1 ¹⁵ / ₁₆ "	15 lbs.
1¾"	MIL-H-24606B-TPU	600 PSI	300 PSI	2 ³ / ₁₆ "	17 lbs.
2½"	MIL-H-24606B-TPU	600 PSI	300 PSI	3"	29 lbs.
4"	MIL-H-24606B-TPU	600 PSI	300 PSI	4 ¹⁷ / ₃₂ "	54 lbs.

Poly-Cord™ Ultra-Shield™ Friction Fighter System™ and Dura-Thane™ are all trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2019A

NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454

Tel: 805.922.7076 • Fax: 805.922.0086

NAFHC.com

